

{ Hand Carry/Portable }

Inverters



07/07/08

1700-3200-4300 Maximum Wattage



GEN-1700-iMSO



GEN-4300-iMSO

Additional Features:



- Low oil level shutdown engine
- Inverter technology reduces size, weight, noise and fuel consumption
- Produces quality AC power for sensitive electronic equipment
- Idle control
- Special vibration control and low-tone mufflers further reduce noise
- USDA/USFS approved spark arrestors
- Battery charging
- Fuel shutoff valve
- Circuit breaker protected
- Meets CARB and EPA emission standards

3200 & 4300 Watt Additional Features:

- Sound reducing materials are highly fire-resistant
- Roll cage design with four wheels
- Electric start (battery not included)
- Voltmeter/hour meter
- Fuel Gauge
- RV application advantage -will run an air conditioner unit (15,000 btu), refrigerator and microwave (3200 watt model)*
- RV application advantage -will run an air conditioner unit (15,000 btu), refrigerator and microwave plus interior lights (4300 watt model)*

**Based on tests conducted on a 2005 5th- wheel camper. Test results are available. Individual test results could vary depending on condition and efficiency of appliance.*

Specifications:

Model #	GEN-1700-iMSO	GEN-3200-iMSO	GEN-4300-iMSO	
Max AC Output	1,650 watts	3,200 watts	4,300 watts	 <p>GFCI 5-20R</p>
Rated AC Output	1,350 watts	2,800 watts	3,800 watts	
HP/Displacement	2.8/86cc	7.0/211 cc	9.0/265 cc	
Engine	Subaru OHV	Subaru OHC	Subaru OHC	
Frequency/Voltage	60Hz/120V	60Hz/120V	60hz/120V	
Max. amps (120V)	13.8	26.7	35.8	
Cont. amps (120V)	11.2	23.3	31.7	
Receptacles	120V, 20A GFCI duplex	120V, 20A GFCI duplex 120V, 30A twist lock	120V, 20A GFCI duplex 120V, 30A twistlock	
Main circuit breaker	Electronic circuit protection	Electronic circuit protection	Electronic circuit protection	
Rated speed	4,200 rpm	3,600 rpm	3,600 rpm	
Decibel rating	59	58	62	 <p>L5-30R 125 VAC</p>
Fuel capacity	1.1 gallon	3.7 gallon	4.2 gallon	
Run time (at full load)	3.5 hours	5.5 hours	5.6 hours	
Dim. (LxWxH)	19.3in.x11.6in.x17.5in.	21in.x18.9in.x22.9 in.	22.8in.x20.7in.x24.3in.	
Shipping weight	55 lbs	143 lbs	174 lbs	
Net weight	44.5 lbs	131 lbs	162 lbs	

*Inverter generator ratings represent no-load sound levels.
Rating represents minimum noise level rating.*

Option: RV Generator Adaptor -30A/125V female/male. Use to connect RV cordsets to 30A generators. Available on GEN-3200-iMSO and GEN-4300-iMSO models